



**CP 500**

**STRAPPING TOOL**

**CYKLOP**<sup>®</sup>  
GLOBAL PACKAGING SOLUTIONS

STRAPPING  
WRAPPING  
CODING  
TAPING

When strapping heavy, flat packages and transporting goods is the highest priority, the CP 500 offers optimal security, especially with loads that want to “settle”. The pneumatic high-performance hand tool is relatively light and easy to operate and applies tension to the strapping band of up to 5,000 N. This makes it a strong alternative to strapping with steel strap. When the Cyklop PET strap is used, an unsurpassed grip and security of the load is achieved.

**Advantages**

- For PP 9 - 16 mm and PET strap 9 - 19 mm
- Ease of use
- Ergonomic design
- Tension up to 5,000 N
- Pneumatically powered

**Options**

- Steel plate for wear protection (concrete and stone industry)
- Universal suspension for stationary strapping



Technical specifications:	
Strapping material	PP strap 9 -16 mm PET strap 9 - 19 mm
Dimensions (LxWxH)	300 x 155 x 200 mm
Weight	5.6 kg
Operation	Manual
Seal	Friction fused weld
Tension	Up to 5.000 N
Insertion	Strap on strap
Air pressure supply	G 1/4"; maintenance kit with filter, regulator and oil mist is absolutely required
Maximal air pressure	6,0 bar